

INNOVATIVE SOLUTIONS FOR SMART PEOPLE



SYR Filling Station MOBIFILL

Filling of heating
systems and water
conditioning to go

MOBIFILL and the SYR cartridge system

The SYR MOBIFILL filling station ensures convenient and inexpensive mobile initial filling of heating systems as well as heating water conditioning and refilling of the installation at different points of use. Simply screw the MOBIFILL onto the required cartridge for water conditioning. Cartridges for the filling with softened water (HWE), fully demineralized water (HVE) or fully demineralized water with pH stabilization (HVE Plus) are available in 2.5 l, 4 l and 7 l. Exchange granules are available for all cartridges.

Digital capacity control

Thanks to the digital capacity control you can have an eye on the expected capacity and the residual value at all times. Even in case of changing initial hardness in different areas of supply, you are on the safe side and flexible by simply adjusting the parameter settings.

MOBIFILL connection

The DVGW-tested SYR backflow preventers STBA 200 and STBA 220 are perfect fits for the connection of the mobile filling station. You can thus properly protect your drinking water installation during the filling process.



After the initial filling

Safe and stationary refilling

By installing the All-in-One Connection Center (integrated backflow preventer) and the corresponding 2.5 l cartridge, you will ensure that the system is permanently filled with conditioned water.



MOBIFILL Filling Station

- convenient carrying recess for easy handling
- digital capacity control
- connection to the SYR cartridge system
- flexible connection hoses (included in delivery)
- ideal combination with SYR backflow preventers STBA 200 and 220

Specifications MOBIFILL

max. operating pressure	6 bar
max. operating temperature	30 °C (input) 65 °C (output)
fluid	drinking water
max. filling capacity	0.5 m ³ /h (0.3 m ³ /h with 2.5 l cartridge)
serial no.	3200.00.040