

The new LEX Plus 10 S Connect: Our soft water comfort model is now available with a sandwich-type connecting fitting.

Our compact soft water system LEX Plus 10 Connect is now available with a sandwich-type connecting fitting (S) combining two of our SYR valve stars: if a potable water filter from the DRUFI system is already mounted in the pipe, the new LEX Plus 10 S Connect will turn two separate appliances into one compact water filtering and softening unit. Simply remove the DRUFI, mount the connecting fitting with the integrated blending device onto the flange, remount the Drufi and connect both hoses of the LEX Plus 10 Connect. That's it – simply brilliant.

Sandwich-type connecting fitting with blending unit



Push-in connection

Glass-display

Illuminated
salt tank

- With a sandwich-type connecting fitting to connect the DRUFI and the LEX Plus 10 Connect at the same time
- Semi-automatic, easy start-up
- Torsion-resistant connection due to new plug system
- Noticeable soft water
- Web-enabled, controllable via SYR App
- User-friendly control with glass-display
- Illuminated salt tank
- Fits SYR's universal flange
- Tundish included



Technical specifications

Operating pressure	Min. 2 bar, max. 8 bar
Operating temperature	Min. 5 °C, max. 30 °C
Ambient temperature	Min. 5 °C, max. 40 °C
Fluid	Drinking water
Power supply	230V / 50 Hz / 6 W
Nominal capacity	22 m³ x °dH
Nominal flow rate DIN 14743	1.5 m³/h
DIN 19636 of 20 °dH with 8 °dH	2.3 m³/h
Pressure loss at nominal flow rate	1.0 bar
Protection class	IP 54



Innovative solutions for smart people