

# Our export hit is simply good. Effective protection against lime formation available in three versions: SYR's LEXsmart water softeners.



## WiFi-enabled (optional)



## Single water softening systems LEXsmart

- Touch-display with easy menu navigation
- Compact control unit
- Analysis and statistics feature
- Adjustment of the regeneration intervals to consumption habits
- WiFi-enabled with the optional USB-stick, then controllable via the SYR App
- Connection equipment and bypass valve included

## Compact control unit

## Analysis and statistics feature



### Technical specifications

Operating pressure	Min. 2 bar, max. 8 bar		
Operating temperature	Min. 5 °C, max. 30 °C		
Ambient temperature	Min. 5 °C, max. 40 °C		
Fluid	Drinking water		
Power supply	6 W / 230V / 50 Hz		
	5 liters	12 liters	20 liters
Flow rate at $\Delta p$ 1.0 bar	2.1 m³/h	2.5 m³/h	2.8 m³/h
Capacity exchanger resin (in m³)	10 x °dH	24 x °dH	40 x °dH

Short-term flow rate with which the ion exchanger can be operated. Very hard water can reduce the indicated nominal flow rate.

Serial number LEXsmart 5 l  
LEXsmart 12 l  
LEXsmart 20 l



**Innovative solutions for smart people**