

Compact and flexible: SYROBLOC for safe and quick installation



SYROBLOC DN 15

For water heaters
up to 200 litres

SYROBLOC DN 20

For water heaters from
200 up to 1000 litres



- **Compact single unit**
- **Flexible installation: allows for angle or in-line assembly**
- **Wear-resistant stainless steel seat**

Connecting pressurised water heaters has never been so easy. The safety groups SYROBLOC DN 15 and DN 20 offer a compact solution, which includes all required elements: an isolating valve, a check valve with test port, a pressure gauge connection and a membrane pressure relief valve. Both SYROBLOC versions are also available with a pressure reducing valve. Installation is finished in no time with only two connections. You automatically comply with EN 1488 and can fully rely on the proven SYR quality.



SMART IDEAS FOR CLEVER PEOPLE

SYROBLOC: A great combination

The SYROBLOC safety groups are designed for the connection of all pressurised potable water heaters – no matter, how they are heated, directly or indirectly, with electricity, gas, fuel oil or solid fuels: SYROBLOC DN 15 for water heaters up to 200 litres and SYROBLOC DN 20 for water heaters from 200 to 1000 litres. Both safety groups have one important thing in common: you save time and money. On the one hand, the time needed for installation is considerably reduced, as the time-consuming single assembly of the various parts is no longer required. On the other hand, you also save money, since the compact safety groups are less cost-intensive than the single components altogether.

SYROBLOC DN 15 and DN 20: two safety groups for all water heaters

Quality that pays off

The SYROBLOC offers best proven SYR quality in the smallest details. Example: the new stainless steel seat of the pressure relief valve is 100% resistant to wear and withstands water with a high lime content.

Flexible installation

The design of the pressure relief valve allows for angle or in-line installation.

Both SYROBLOC models are easy to service (cartridge system). The SYR module system allows an unproblematic exchange of the various components.



One unit, many benefits:

- **Compact unit: quick installation, reduced risk of leakage, simple storage**
- **Cartridge system for easy servicing**
- **Fulfilment of all requirements laid down in EN 1488**
- **Flexible installation: allows for angle or in-line assembly**
- **Long service life: valve seat made of stainless steel**

Technical specifications

Inlet pressure	Max. 10 bar
Operating pressure	Max. 80 % of the response pressure of the pressure relief valve
Nominal size	DN 15 und DN 20
Design	Angle and in line assembly
Mounting position	Any
Fluid	Potable water
Field of application	Protection of water heaters up to 200 l (DN 15), from 200 l to 1000 l (DN 20)



Registrier-Nr. SQ-9001BM6003
DIN EN 9001:2000

